



### Drill Pipe Recommendation Chart

Size	Connection	Weight	Grade	TJ ID	Tube ID	Motor	Spring Head	Finger Head	Lance
2-3/8"	2-3/8"IF/NC26	6.65#	S-135	1.750"	1.815"	3150	SRA-1470	1840	1/2"
2-7/8"	2-7/8" HTPAC	10.40#	E-75	1.500"	2.151"	3150	SRA-1470	NA	1/2"
2-7/8"	2-7/8" HTPAC	10.40#	S-135	1.500"	2.151"	3150	SRA-1470	NA	1/2"
2-7/8"	2-7/8" HTPAC	10.40#	G-105	1.500"	2.151"	3150	SRA-1470	NA	1/2"
2-7/8"	2-3/8HTSLH90	10.40#	S-135	1.975"	2.151"	3150	SRA-1470	NA	1/2"
2-7/8"	HT-26	10.40#	S-135	1.750"	2.151"	3150	SRA-1470	NA	1/2"
2-7/8"	NC26 2-3/8 IFSH	10.40#	X-95	1.500"	2.151"	3150	SRA-1470	NA	1/2"
2-7/8"	NC26 2-3/8 IFSH	10.40#	S135	1.500"	2.151"	3150	SRA-1470	NA	1/2"
2-7/8"	2-7/8" AOH	10.40#	S-135	2.156"	2.151"	3200	SRA-1870	NA	3/4"
2-7/8"	2-7/8"IF NC31	10.40#	E-75	2.125"	2.151"	3200	SRA-1870	NA	3/4"
2-7/8"	2-7/8" AOH	10.40#	X-95	2.156"	2.151"	3200	SRA-1870	NA	3/4"
2-7/8"	2-7/8"IF NC31	10.40#	S-135	2.000"	2.151"	3200	SRA-1870	NA	3/4"
3-1/2"	3-1/2"IF NC38	13.30#	E-75	2.688"	2.764"	3250	SRA-3370	3370	1"
3-1/2"	3-1/2"IF NC38	13.30#	X-95	2.688"	2.764"	3250	SRA-3370	3370	1"
3-1/2"	3-1/2"IF NC38	13.30#	XD-105	2.563"	2.764"	3250	SRA-3370	3370	1"
3-1/2"	3-1/2"IF NC38	13.30#	S-135	2.563"	2.764"	3250	SRA-3370	3370	1"
3-1/2"	3-1/2" HT-38	13.30#	S-135	2.563"	2.764"	3250	SRA-3370	3370	1"
3-1/2"	3-1/2" XT-38	13.30#	S-135	2.563"	2.764"	3250	SRA-3370	3370	1"
3-1/2"	3-1/2"IF NC38	15.50#	X-95	2.563"	2.602"	3250	SRA-3370	3370	1"
3-1/2"	3-1/2"IF NC38	15.50#	XD-105	2.563"	2.602"	3250	SRA-3370	3370	1"
3-1/2"	3-1/2"IF NC38	15.50#	S-135	2.563"	2.602"	3250	SRA-3370	3370	1"
3-1/2"	NC-38	15.50#	S-135	2.563"	2.602"	3250	SRA-3370	3370	1"
3-1/2"	XT-38	13.30#	S-135	2.563"	2.602"	3250	SRA -3370	3370	1"
4"	XT-39	14.00#	S-135	2.688"	3.340"	3250	SRA-3270	3270	1"
4"	XT-39	15.70#	XD-105	2.688"	3.340"	3250	SRA-3270	3270	1"
4"	4" FH NC40	14.00#	S-135	2.688"	3.340"	3250	SRA-3270	3270	1"
4"	HT-40	14.00#	S-135	2.688"	3.340"	3250	SRA-3270	3270	1"
4"	XT-39	14.00#	S-135	2.813"	3.340"	3250	SRA-3270	3270	1"
4"	XT-M 38	14.00#	S-135	2.688"	3.340"	3250	SRA-3270	3270	1"
4-1/2"	4-1/2"XH NC46	16.60#	S-135	3.000"	3.826"	3275	SRA-970	970	1"
4-1/2"	4-1/2"XH NC46	20.00#	S-135	3.000"	3.640"	3275	SRA-970	970	1"
5"	4-1/2"IF NC50	19.50#	S-135	3.250"	4.276"	3300	SRA-770	770	1"
5"	XT-50	19.50#	S-136	3.750"	4.276"	3300	SRA-770	770	1"
5"	4-1/2"IF NC50	25.60#	S-135	3.250"	4.000"	3300	SRA-770	770	1"
5-1/2"	5-1/2" FH	21.90#	S-135	3.500"	4.778"	3350	SRA-5770	770 SA	1"
5-1/2"	5-1/2" FH	24.70#	S-135	3.000"	4.670"	3350	SRA-5770	770 SA	1"
5-7/8"	XT-57	23.40#	S-135	4.250"	5.153"	3400	SRA-5770	770 SA	1"
5-7/8"	XT-57	26.30#	S-135	4.250"	5.045"	3400	SRA-5770	770 SA	1"
5-7/8"	CTM57	28.70#	S-135	4.250"	4.875"	3400	SRA-5770	770 SA	1"